

Technical Information

No. FO 5095

Edition: 06/13 - subject to change

Substitutes: Edition 07/02

Status: valid

Mercury Short Arc Lamp
for Microlithography

HBO[®] 1500 W/PIL

■ Product description

The OSRAM HBO[®] 1500 W/PIL is a long life direct current mercury short arc i-line lamp designed for the manufacture of integrated circuits (microlithography). This lamp type emits a very high radiant intensity in the ultraviolet and visible wavelength range and is designed and optimized for use in ASML equipment (PAS 5500/22, /100, /100B, /TFH 100).

■ Technical data

Order reference	HBO [®]	1500 W/PIL
Rated lamp wattage	W	1,500
Rated lamp voltage	V	23
Rated lamp current (=)	A	66
Ignition voltage (cold)	kV _s	max. 20
Radiant intensity (wave length range 365 ± 2,5nm)	mW/sr	4,850
Electrode gap e (cold)	mm	4
Lamp length (overall) l ₁	mm	max. 273
Lamp length l ₂	mm	240 / max. 242
Bulb diameter d	mm	46
LCL a	mm	118
Guaranteed life	h	See warranty sheet
Lamp mass	g	450

Base

- Cathode: SFc 27-10/35
- Anode: SFc 30-6/25 with cooling fins and cable connection

■ Lamp operation

Maximum permissible base temperature	°C	200
Cooling	forced base cooling, cooling fins on anode base	
Burning position	vertical, Anode (+) underneath	

■ Safety Instruction

Due to their high luminous efficacy, the UV radiation which they emit and the high pressure within the lamp, HBO[®] lamps must be operated within enclosed, purpose-built housings. When a lamp breaks, mercury is released. Particular safety regulations must be paid attention (for details please request technical information sheet no. FO 4574).

