

PRODUCT REQUIREMENT SHEET

MEASURING VOLTAGE	At rated voltage : 24 V (stabilization 3 min)
MEASURING POSITION	180° (vertical-cap up)
LIFE TEST POSITION	180° (vertical-cap up)
SWITCHING CYCLE	Continuous, twice daily off during 15 min
AGEING	1 hour at rated voltage

CHARACTERISTICS	VALUE	UNIT	TOL.	SPECIFICATIONS	AQL
WATTAGE	40	W	nom	± 4% + 0,5W	2,5 %
	42,1		maxi		
LUMINOUS FLUX	605	Lm	nom	Mini 93%	4 %
	563		mini		
EFFICIENCY	15,1	Lm/W		Indicative Value	
LUMEN MAINTENANCE	85	%		After 75% of nominal life time	4 %
COLOR TEMPERATURE	N.A	°K		Not applicable	
LIFE TIME	1150	H	nom		6,5 %
	700		mini		
LAMPS DIMENSIONS	72,5	mm	maxi	See SH-110 8225 041 20500	1,5 %
MOUNTING	1 pigtail				
CAP DIMENSIONS	B22d/25*26			IEC 60061-1	
TORQUE TEST	3	Nm	mini	IEC 60432-1	0,65%
CAP TEMPERATURE RISE	N.A	°C	maxi	IEC 60432-1 Not applicable	
WEIGHT	21	g		Indicative Value	
ENERGIE EFFICIENCY LABEL (EEL)	N.A			Directive 98/11/CE	
ATTRIBUTIVE REQUIREMENT	LV 075-006 Sum of critical defects Sum of major inoperative defects Sum of minor defects				0 0.65% 2.5%



Supersedes : création d'après 9214 205 20500 du 06/02/2008	P45 BV	40W	8225 041 20500	17/04/2012
	B22d/25*26	24V		
REF: PDM-GL-2012-10		CLEAR		SH 190-1
NOM : Éric SIRANTOINE	VALIDATION : E. HUET		DOCUMENTATION DR. FISCHER PONT-A-MOUSSON	