



CorePro LEDcapsule LV



CorePro LEDcapsuleLV 1.8-20W G4 830

The CorePro LEDcapsule is a true alternative to the halogen capsule. It is particularly suitable for task lighting and decorative applications in homes, shops, hotels and restaurants. Compatible with existing fixtures with G4 holders and designed for retrofit replacement of halogen capsules, CorePro LEDcapsule delivers huge energy savings and minimizes maintenance costs without any compromise on light quality.

Product data

General Information	
Cap-Base	G4
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	300 degree(s)
Luminous Flux	215 lm
Luminous Efficacy (rated) (Nom)	119.00 lm/W
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3000 K
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM) - Flickering value as per	0.4
EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	1
-	

Photobiological safety according to EN 62471	RG1
Photobiological safety according to EN 62471	RGI
Operating and Electrical	
Line Frequency	- Hz
Input Frequency	- Hz
Power Consumption	1.8 W
Lamp Current (Nom)	260 mA
Wattage Equivalent	20 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.6
Voltage (Nom)	ac electronic 12 V
Temperature	
T-Case Maximum (Nom)	80 ℃
Controls and Dimming	
Dimmable	No


Datasheet, 2024, July 15 data subject to change

CorePro LEDcapsule LV

Management and Harrison		
Mechanical and Housing		
Bulb Shape	Capsule	
Approval and Application		
Energy Efficiency Class	Е	
Suitable For Accent Lighting	No	
Energy Consumption kWh/1000 h	2 kWh	
EPREL Registration Number	374874	
CE mark	Yes	
EU RoHS compliant	Yes	
EyeComfort	Yes	
Application Conditions		
can it be used in closed luminaires	No	


CorePro LEDcapsuleLV 1.8-20W G4 830 CorePro LEDcapsuleLV 1.8-20W G4 830 871869976769300	
CorePro LEDcapsuleLV 1.8-20W G4 830 871869976769300	
830 871869976769300	
871869976769300	
929002389102	
929002389102	
1	
0.008 kg	
8718699767693	
12	
8718699767709	

Dimensional drawing




Product	D	С
CorePro LEDcapsuleLV 1.8-20W G4 830	13 mm	35 mm

Photometric data








General uniform lighting - CorePro LEDcapsuleLV 1.8-20W G4 830


CorePro LEDcapsule LV


Photometric data



Spectral Power Distribution Colour - CorePro LEDcapsuleLV 1.8-20W G4 830

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro LEDcapsuleLV 1.8-20W G4 830



© 2024 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.